QuickSpecs

Overview

Models

HP ProCurve 10-GbE 2-Port CX4 al Module

HP ProCurve 10-GbE 2-Port SFP+ al Module

HP ProCurve 10-GbE al Interconnect

J9165A



QuickSpecs

Technical Specifications

HP ProCurve 10-GbE 2-Port CX4 al Module

(J9149A

10-GbE module with two fixed CX4 ports for HP ProCurve Switch 2910al

Series)

Ports 2 CX4 10-GbE ports (IEEE 802.3ak Type 10Gbase-CX4)

Duplex: full only

Physical characteristics Dimensions: 4.11(d) x 4.18(w) x 1.4(h) in. (10.44 x 10.62 x 3.56 cm)

Weight: 0.35 lb. (0.16 kg)

Environment Operating temperature: 32°F to 122°F (0°C to 5°0C)

Operating relative humidity: 15% to 95% @ $104^{\circ}F$ ($40^{\circ}C$), non-condensing Non-operating/Storage temperature: $-40^{\circ}F$ to $158^{\circ}F$ ($-40^{\circ}C$ to $70^{\circ}C$) Non-operating/Storage relative humidity: 15% to 95% @ 149F ($65^{\circ}C$), non-

condensing

Cabling Maximum distance:

15 m using CX4 cable

300 m using optical media converters and multimode fiber cable

Notes Use CX4 10-GbE cable (0.5 m-15 m) or HP ProCurve 10-GbE CX4 Media

Converter (J8439A). No CX4 cables are included with this module.

HP ProCurve 10-GbE 2-port SFP+ al Module

(J9008A)

10-GbE module with two fixed SFP+ slots for HP ProCurve Switch 2910al

Series

Ports 2 open 10-GbE SFP+ transceiver slots

Physical characteristics Dimensions: 4.0(d) x 4.18(w) x 1.4(h) in. (10.16 x 10.62 x 3.56 cm)

Weight: 0.35 lb. (0.16 kg)

Environment Operating temperature: 32F to 122F (0C to 50C)

Operating relative humidity: 15% to 95% @ 104F (40C), non-condensing

Non-operating/Storage temperature: -40F to 158F (-40C to 70C)

Non-operating/Storage relative humidity: 15% to 95% @ 149F (65C), non-

condensing

HP ProCurve 10-GbE al

Interconnect Kit (J9165A)

Two 1 port CX4 modules for short distance interconnection - includes 1/2 meter CX4 cable - for ProCurve Switch 2910al

series)

Physical characteristics

Dimensions: 4.11(d) x 4.18(w) x 1.4(h) in. (10.44 x 10.62 x 3.56 cm)

Weight: 0.31 lb. (0.14 kg)

Environment Operating temperature: 32F to 122F (0C to 50C)

Operating relative humidity: 15% to 95% @ 104F (40C), non-condensing

Non-operating/Storage temperature: -40F to 158F (-40C to 70C)

Non-operating/Storage relative humidity: 15% to 95% @ 149F (65C), non-

condensing

Notes ProCurve Switch bl 10-GbE Interconnect Kit includes two 1-port 10-GbE

CX4 compatible Interconnect modules for short-distance connectivity using

the 0.5 m CX4 cable provided.

To learn more, visit www.hp.com/go/procurve

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

