

[Get a Quote](#)

Overview

Cisco 300 series switch delivers the ideal combination of price, performance, and capabilities in a solution designed specifically for small businesses. This broad portfolio of affordable managed switch provides a powerful foundation to support your business network.

Quick Specs

Figure 1 shows the appearance of SG300-28PP.



Table 1 shows the Quick Specs.

Jumbo Frame Support:	9 KB
Routing Protocol:	Static IPv4 routing
Minimum Storage Temperature:	-4 F
Depth:	10.1 inches
MTBF:	310,755 hours (@40C)
Cables Included:	1x Serial Cable
Capacity:	4K Active VLANs
Height:	1.45 inches
Maximum Operating Temperature:	104 F
MAC Address Table Size:	16k entries
Width:	11 inches
Enclosure Type:	Desktop, rack-mountable - 1U
Maximum Storage Temperature:	158 F
Ports:	26 x 10/100/1000 + 2 x combo Gigabit SFP
Device Type:	Switch - 28 ports - L3 - managed
Humidity Operating Range:	10-90% (non-condensing)
Weight:	8.71 lbs
Minimum Operating Temperature:	32 F

Interfaces:	8 x 10Base-T/100Base-TX - RJ-45 - PoE 1 x console - 9 pin D-Sub (DB-9) - management 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 / SFP (combo)
Humidity Storage Range:	10-90% (non-condensing)
Flash Memory:	16 MB
Voltage Required:	AC 120/230 V (50/60 Hz)
Performance:	Switching capacity : 56 Gbps Forwarding performance (64-byte packet size) : 41.67 Mpps
Power Device:	Power supply - internal
Power Over Ethernet (PoE):	POE and POE+
Status Indicators:	Link activity, port transmission speed, system
Ram:	128 MB
Authentication Method:	Secure Shell (SSH), RADIUS, TACACS+

Get More Information

Do you have any question about the Cisco SG300-28PP?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

SG300-28PP Specification	
Jumbo Frame Support:	9 KB
Routing Protocol:	Static IPv4 routing
Minimum Storage Temperature:	-4 F
Depth:	10.1 inches
MTBF:	310,755 hours (@40C)
Cables Included:	1x Serial Cable
Capacity:	4K Active VLANs
Height:	1.45 inches
Maximum Operating Temperature:	104 F
MAC Address Table Size:	16k entries
Width:	11 inches
Enclosure Type:	Desktop, rack-mountable - 1U
Maximum Storage Temperature:	158 F
Ports:	26 x 10/100/1000 + 2 x combo Gigabit SFP
Device Type:	Switch - 28 ports - L3 - managed
Humidity Operating Range:	10-90% (non-condensing)
Weight:	8.71 lbs

Minimum Operating Temperature:	32 F
Interfaces:	8 x 10Base-T/100Base-TX - RJ-45 - PoE 1 x console - 9 pin D-Sub (DB-9) - management 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 / SFP (combo)
Humidity Storage Range:	10-90% (non-condensing)
Flash Memory:	16 MB
Voltage Required:	AC 120/230 V (50/60 Hz)
Performance:	Switching capacity : 56 Gbps Forwarding performance (64-byte packet size) : 41.67 Mpps
Power Device:	Power supply - internal
Power Over Ethernet (PoE):	POE and POE+
Status Indicators:	Link activity, port transmission speed, system
Ram:	128 MB
Authentication Method:	Secure Shell (SSH), RADIUS, TACACS+

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com